

# Type K



## Radiatoare de baie Thernal Trend – Date tehnice

Type description	Height H [mm]	Length L [mm]	Thread pitch [mm]	t <sub>1</sub> /t <sub>2</sub> [°C]	Q[W] pro t <sub>j</sub> [°C]			Thermal exponent n [-]	Water volume n [l]	Rec. Radiator input power [W]	
					18	20	22				
K 400 / 800	800	400	370	90/70	339	325	311	1,24246	2,40	200	
				75/65	272	259	246				
				55/45	149	137	126				
K 450 / 800		450	420	420	90/70	372	357	342	1,24246	2,55	200
					75/65	299	284	271			
					55/45	164	151	139			
K 500 / 800		500	470	470	90/70	404	388	372	1,24246	2,70	300
					75/65	325	309	294			
					55/45	178	164	151			
K 550 / 800	550	520	520	90/70	436	418	401	1,24246	2,90	300	
				75/65	351	334	318				
				55/45	191	177	162				
K 600 / 800	600	570	570	90/70	468	449	431	1,24246	3,05	300	
				75/65	376	358	340				
				55/45	206	190	174				
K 750 / 800	750	720	720	90/70	559	537	515	1,24246	3,55	300	
				75/65	449	428	406				
				55/45	245	226	208				
K 400 / 1200	1200	400	370	90/70	516	495	475	1,24251	3,60	300	
				75/65	415	395	376				
				55/45	227	210	192				
K 450 / 1200		450	420	420	90/70	567	544	522	1,24251	3,90	300
					75/65	455	434	412			
					55/45	249	230	211			
K 500 / 1200		500	470	470	90/70	616	591	567	1,24251	4,15	300
					75/65	495	471	448			
					55/45	270	262	229			
K 550 / 1200		550	520	520	90/70	664	638	611	1,24251	4,40	400
					75/65	534	509	484			
					55/45	292	276	248			
K 600 / 1200		600	570	570	90/70	713	685	657	1,24251	4,65	400
					75/65	573	546	519			
					55/45	314	290	265			
K 750 / 1200		750	720	720	90/70	852	818	784	1,24251	5,40	500
					75/65	685	652	620			
					55/45	375	346	317			
K 400 / 1500	1500	400	370	90/70	659	633	606	1,24256	4,55	400	
				75/65	530	504	479				
				55/45	290	267	245				
K 450 / 1500		450	420	420	90/70	724	695	666	1,24256	4,90	400
					75/65	582	554	526			
					55/45	318	293	269			

K 500 / 1500		500	470	90/70	786	755	723	1,24256	5,20	400
				75/65	632	602	572			
				55/45	345	318	292			
K 550 / 1500		550	520	90/70	849	814	781	1,24256	5,50	500
				75/65	732	649	617			
				55/45	400	344	316			
K 600 / 1500		600	570	90/70	911	874	838	1,24256	5,80	500
				75/65	732	697	662			
				55/45	400	396	339			
K 750 / 1500		750	720	90/70	1088	1044	1001	1,24256	6,80	600
				75/65	874	833	792			
				55/45	478	441	405			
K 400 / 1800	1800	400	370	90/70	802	770	738	1,2426	5,45	400
				75/65	645	614	584			
				55/45	353	326	299			
K 450 / 1800	1800	450	420	90/70	881	846	811	1,2426	5,85	500
				75/65	708	674	641			
				55/45	387	357	328			
K 500 / 1800	1800	500	470	90/70	957	919	881	1,2426	6,20	500
				75/65	769	732	696			
				55/45	420	388	356			
K 550 / 1800	1800	550	520	90/70	1033	991	951	1,2426	6,60	500
				75/65	830	791	752			
				55/45	454	419	385			
K 600 / 1800	1800	600	570	90/70	1109	1064	1020	1,2426	7,00	600
				75/65	891	848	806			
				55/45	487	450	413			
K 750 / 1800	1800	750	720	90/70	1324	1271	1219	1,2426	8,10	700
				75/65	1064	1014	964			
				55/45	582	538	493			